


1.Aluminum Bars

典型合金 Typical Alloys
2014、2017、2024、2219、2A02、2A12、2A14、2A50
5005、5052、5083、5A06、5A12
6005、6005A、6008、6060、6061、6063、6082、6101、6101B、6106、6A02
7003、7005、7020、7021、7050、7055、7075、7A04、7A52、7N01

2.Specification

名称 Product	D/S(mm)			
	2XXX系、5XXX系、7XXX系合金 2XXX, 5XXX and 7XXX alloys		6XXX系合金 6XXX series alloys	
	最小 Min	最大 Max	最小 Min	最大 Max
 D 圆棒 Round bar	20	400 ^①	20	400 ^②
 S 六角棒 Hexagonal bar	40	350 ^①	40	350 ^②
 S 方棒 Square bar	40	300 ^①	40	300 ^②
注：① 2XXX系、7XXX系合金T3511、T73511、T6511、T74511、T76511状态最大为120； Note: The maximum states of 2XXX and 7XXX alloys T3511, T73511, T6511, T74511 and T76511 are 120. ② 6XXX系合金T6511状态最大为160。 The maximum state of 6XXX alloy T6511 is 160.				

3.Rectangular Bar Specification

名称 Product	合金 Alloy	t/mm	W/mm	米重(Kg/m) Weight
 t W 矩形棒(排材) Rectangular bar	2XXX系、5XXX系、7XXX系 2XXX, 5XXX and 7XXX series	15~300	80~500	12~240
	6XXX系 6XXX series	5~300	50~700	3~240

